



AUTOYOU
ESSENTIAL VEHICLE PROTECTION

SAFETY DATA SHEET ALLOY WHEEL CLEANER

According to the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practise, 2021.

SECTION 1: Identification: Product identifier and chemical identity

Product identifier

Product name Alloy Wheel Cleaner

Product No. 237-5

Relevant identified uses of the substance or mixture and uses advised against

Application Cleaning agent.

Uses advised against For professional use only. This product is not recommended for any industrial, professional or consumer use other than the Identified uses above.

Details of the supplier of the safety data sheet

Supplier AutoYou Pty Ltd
450 Graham St
Port Melbourne
VIC 3207
Australia
www.autoyou.com.au
Tel: 1300 826 801 (Mon to Fri, 09:00 - 17:00 AEST) (General Information. Transport Information. Mild Medical Information)
enquiries@autoyou.com.au

Contact Person Mr. Tao Lim

Emergency telephone number General Information. Transport Information. Mild medical Information:-
Tel: 1300 826 801 (Mon to Fri, 09:00 - 17:00 AEST)

National emergency telephone number Poison Information Hotline: 13 11 26

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Corr. 1C - H314 Eye Dam. 1 - H318

Environmental hazards Not Classified

Label elements

ALLOY WHEEL CLEANER

Hazard pictograms



Signal word

DANGER

Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P264 Wash contaminated skin thoroughly after handling.
 P280 Wear protective gloves.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P362+P364 Take off contaminated clothing and wash before reuse.
 P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

For professional users only.

Contains

C9-C11 Alcohol ethoxylate (6), Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO), sodium hydroxide, 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Other hazards

This product does not contain any substances classified as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

SECTION 3: Composition and information on ingredients

Mixtures

Tetrapotassium Pyrophosphate CAS number: 7320-34-5	3<5%
Classification Eye Irrit. 2A - H319	
Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO) CAS number: 160901-19-9	2<3%
Classification Acute Tox. 4 - H302 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412	
C9-C11 Alcohol ethoxylate (6) CAS number: 68439-46-3	2<3%
Classification Acute Tox. 4 - H302 Eye Dam. 1 - H318	

ALLOY WHEEL CLEANER

sodium hydroxide	1.5<1.75%
CAS number: 1310-73-2	
Substance with a Community workplace exposure limit.	
Classification	
Met. Corr. 1 - H290	
Skin Corr. 1A - H314	
Eye Dam. 1 - H318	
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts	1<1.25%
CAS number: 97862-59-4	
Classification	
Eye Dam. 1 - H318	
Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

Description of first aid measures

General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. Chemical burns must be treated by a physician.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
Skin Contact	It is important to remove the substance from the skin immediately. Take off immediately all contaminated clothing. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention. Chemical burns must be treated by a physician.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

ALLOY WHEEL CLEANER

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Corrosive to the respiratory tract. Symptoms following overexposure may include the following: Severe irritation of nose and throat.
Ingestion	May cause chemical burns in mouth, oesophagus and stomach. Symptoms following overexposure may include the following: Severe stomach pain. Nausea, vomiting.
Skin contact	Causes severe burns. Symptoms following overexposure may include the following: Pain or irritation. Redness. Blistering may occur.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Severe corrosive hazard. Water used for fire extinguishing, which has been in contact with the product, may be corrosive.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Very toxic or corrosive gases or vapours.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Regular protection may not be safe. Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for chemical incidents.

Hazchem Code 2W

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

ALLOY WHEEL CLEANER

Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of dust and vapours. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes. Avoid contact with contaminated tools and objects.

Environmental precautions

Environmental precautions

The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. This product is corrosive. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Neutralise with acid. Caution. May generate heat. Following dilution and neutralisation, discharge to the sewer with plenty of water may be permitted. The requirements of the local water authority must be complied with if contaminated water is flushed directly to the sewer. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. This product is corrosive. Immediate first aid is imperative. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

ALLOY WHEEL CLEANER

Storage precautions	Store in accordance with local regulations. Store away from the following materials: Acids. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.
Storage class	Corrosive storage.
Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.

SECTION 8: Exposure controls and personal protection

Control parameters

Occupational exposure limits

sodium hydroxide

Ceiling value: 2 mg/m³

Tetrapotassium Pyrophosphate (CAS: 7320-34-5)

Ingredient comments No exposure limits known for ingredient(s).

Alcohols, C12-13 - branched and linear, ethoxylated (>5 - 10 EO) (CAS: 160901-19-9)

Ingredient comments No exposure limits known for ingredient(s).

C9-C11 Alcohol ethoxylate (6) (CAS: 68439-46-3)

Ingredient comments No exposure limits known for ingredient(s).

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts (CAS: 97862-59-4)

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

ALLOY WHEEL CLEANER

Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. When used with mixtures, the protection time of gloves cannot be accurately estimated. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: >0.2mm The selected gloves should have a breakthrough time of at least 0.5 hours. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Use thin cotton gloves inside natural rubber gloves if there is an allergy risk to natural rubber.
Other skin and body protection	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
Hygiene measures	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.
Environmental exposure controls	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Fluorescent. Green.
Odour	Lemon.
Odour threshold	Not available.
pH	pH (concentrated solution): ~ 13.6 pH (diluted solution): ~ 10.2 @ 1%
Melting point	~ 0°C

ALLOY WHEEL CLEANER

Initial boiling point and range	~100°C @ °C @ 760 mm Hg
Flash point	Not applicable.
Evaporation rate	Not available.
Flammability Limit - Lower(%)	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	~1.050 @ (20°C)°C
Solubility(ies)	Soluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not applicable.
Decomposition Temperature	Not available.
Viscosity	~ 1 cSt @ °C
Oxidising properties	Not applicable.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.
Volatile organic compound	This product contains a maximum VOC content of 0 g/litre.

SECTION 10: Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	No potentially hazardous reactions known.
Conditions to avoid	There are no known conditions that are likely to result in a hazardous situation.
Materials to avoid	Acid anhydrides. Acids. Phenols, cresols.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Corrosive gases or vapours.

SECTION 11: Toxicological information

Information on toxicological effects

Other health effects	There is no evidence that the product can cause cancer.
<u>Acute toxicity - oral</u>	
Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
ATE oral (mg/kg)	10,638.3
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - inhalation</u>	

ALLOY WHEEL CLEANER

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Animal data	Skin Corr. 1C - H314 Causes severe burns.
Human skin model test	Scientifically unjustified.
Extreme pH	≥ 11.5 Corrosive.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Eye Dam. 1 - H318 Corrosive to skin. Corrosivity to eyes is assumed.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Corrosive to the respiratory tract. Symptoms following overexposure may include the following: Severe irritation of nose and throat.
Ingestion	May cause chemical burns in mouth, oesophagus and stomach. Symptoms following overexposure may include the following: Severe stomach pain. Nausea, vomiting.
Skin Contact	Causes severe burns. Symptoms following overexposure may include the following: Pain or irritation. Redness. Blistering may occur.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.
Acute and chronic health hazards	No specific long-term effects known.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	No specific target organs known.

ALLOY WHEEL CLEANER

Medical Symptoms No specific symptoms noted, but this chemical may still have adverse health impact, either in general or on certain individuals.

Medical considerations Skin disorders and allergies.

Toxicological information on ingredients.

Tetrapotassium Pyrophosphate

Other health effects There is no evidence that the product can cause cancer.

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 7,783.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,066.0

Species Rat

Skin sensitisation

Skin sensitisation Not sensitising.

Reproductive toxicity

Reproductive toxicity - development Developmental toxicity: - NOAEL: 1,000 mg/kg, Oral, Rat

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 300 mg/kg, Oral, Rat Not classified as a specific target organ toxicant after repeated exposure.

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment. The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms. The product is not expected to be hazardous to wastewater treatment processes. The product does not contain organic complexing agents with a DOC level of degradation of < 80% after 28 days. The product does not contain organically bound halogen.

Ecological information on ingredients.

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Ecotoxicity Harmful to aquatic life.

ALLOY WHEEL CLEANER

Toxicity Based on available data the classification criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Acute toxicity - aquatic invertebrates Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - microorganisms Not determined.

Acute toxicity - terrestrial Not determined.

Ecological information on ingredients.

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Acute aquatic toxicity

Acute toxicity - fish LC50, 96 hours: ~ 1.11 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 1.9 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 2.4 mg/l, Freshwater algae

Acute toxicity - microorganisms EC₀, : 3,000 mg/l, Activated sludge

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOEC, : 0.135 mg/l, Oncorhynchus mykiss (Rainbow trout)

Chronic toxicity - aquatic invertebrates NOEC, : 0.3 mg/l, Daphnia magna

Persistence and degradability

Ecological information on ingredients.

Tetrapotassium Pyrophosphate

Persistence and degradability The product is biodegradable.

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Persistence and degradability The product is biodegradable.

Bioaccumulative potential

Bioaccumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Tetrapotassium Pyrophosphate

ALLOY WHEEL CLEANER

Bioaccumulative Potential The product does not contain any substances expected to be bioaccumulating.

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Bioaccumulative Potential The product does not contain any substances expected to be bioaccumulating.
BCF: 71,

Mobility in soil

Mobility The product is water-soluble and may spread in water systems. The product is non-volatile.

Ecological information on ingredients.

Tetrapotassium Pyrophosphate

Mobility The product is soluble in water.

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,N-C8-18(even numbered) acyl derivs., hydroxides, inner salts

Mobility The product is soluble in water.

Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

Tetrapotassium Pyrophosphate

Other adverse effects The product may contribute to an excessive enrichment of the aquatic environment with nutrients.

SECTION 13: Disposal considerations

Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

UN number

UN No. (ADG) 1824

UN No. (IMDG) 1824

ALLOY WHEEL CLEANER

UN No. (ICAO) 1824

UN proper shipping name

Proper shipping name (ADG) SODIUM HYDROXIDE SOLUTION

Proper shipping name (IMDG) SODIUM HYDROXIDE SOLUTION

Proper shipping name (ICAO) SODIUM HYDROXIDE SOLUTION

Transport hazard class(es)

ADG class 8

ADG label 8

IMDG class 8

ICAO class/division 8

Transport labels



Packing group

ADG packing group III

IMDG packing group III

ICAO packing group III

Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

IMDG Code segregation group 18. Alkalis

EmS F-A, S-B

Hazchem Code 2W

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

ALLOY WHEEL CLEANER

Guidance	<p>The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP). National Code of Practice for the Preparation of Material Safety Data Sheets. Approved Criteria for Classifying Hazardous Substances. Exposure Standards for Atmospheric Contaminants in the Occupational Environment. Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment. National Code of Practice for the Labelling of Workplace Substances. National Model Regulations for the Control of Workplace Hazardous Substances. National Code of Practice for the Control of Workplace Hazardous Substances. National Standard for the Storage and Handling of Workplace Dangerous Goods. National Code of Practice for the Storage and Handling of Workplace Dangerous Goods. Guidance Note for Placarding Stores for Dangerous Goods and Specified Hazardous Substances. Guidance Note for the Assessment of Health Risks Arising from Hazardous Substances in the Workplace. National Standard for the Control of Major Hazard Facilities. National Code of Practice for the Control of Major Hazard Facilities.</p>
-----------------	---

Schedule (SUSMP) Schedule 5. Caution.

Inventories

Australia - AIC

All the ingredients are listed or exempt.

SECTION 16: Any other relevant information

General information	This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.
Training advice	Read and follow manufacturer's recommendations.
Revision	
comments Issued by	<p>NOTE: Lines within the margin indicate significant changes from the previous revision.</p> <p>Prepared by AutoYou Pty Ltd, Tao Lim, 450 Graham St, Port Melbourne VIC 3207, Australia.</p> <p>www.autoyou.com.au lim@autoyou.com.au Tel: 1300 826 801</p>
Revision date	31/05/2022
Revision Supersedes date	23
SDS No.	13/05/2021
SDS status	11028
Hazard statements in full	<p>Approved.</p> <p>H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.